# **B Series Grind**



# **60" Hammermill**

The DZT1460 is a workhorse that out-produces other grinders in its class. Featuring a 14' tub, and up to 1,050 horsepower, it makes short work of C&D material, railroad ties, green waste, stumps, passenger tires and more.

Diamond Z Grinders, Caldwell Idaho

www.diamondz.com

208-585-2929



# **B** Series Grinders









SPECIFICATIONS:

### **DZT1460B**

# DZT1460BL

# DZT1460BTK

| POWER:                            | CAT <sup>®</sup> C27 1,050 HP Tier 4 | CAT <sup>®</sup> C27 1,050 HP Tier 4 | CAT <sup>®</sup> C27 1,050 HP Tier 4 |
|-----------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| TRANSMISSION:                     | Fluid Coupling Drive                 | Fluid Coupling Drive                 | Fluid Coupling Drive                 |
| TRANSPORT DIMENSIONS (L x W x H): | 35'-10" x 11'-11" x 13'-6"           | 45'-9" x 11'-11" x 14'-0"            | 36'-8" x 11'-8" x 11'-9"             |
| OPERATING DIMENSIONS (L x W x H): | 100'-0" x 66'-0" x 32'-0"            | 44'-10" x 14'-0" x 13'-9"            | 44'-10" x 14'-0" x 13'-9"            |
| WEIGHT:                           | 63,000 Lbs.                          | 84,000 Lbs.                          | 74,000 Lbs.                          |
| MILL FEED OPENING:                | 27" x 60"                            | 27" x 60"                            | 27" x 60"                            |
| SCREEN AREA:                      | 3,960 Sq. In.                        | 3,960 Sq. In.                        | 3,960 Sq. In.                        |
| PRODUCTION:                       | Up to 95 TPH/665 YPH                 | Up to 95 TPH/665 YPH                 | Up to 95 TPH/665 YPH                 |



**STANDARD FEATURES:** Fluid coupling mill drive, radio remote control, tool box, engine cover, and super-screw belt lacing. All track-mounted machines come with 24" (600mm) wide pads (20" and 32" also available on most models).

All information subject to change without notice. Please reconfirm any critical details. Productions rates based on customer reports, actual throughput will vary depending on on-site specifics.

1460-0620