

Caterpillar® engine, combined with our aggressive down-cut mill, delivers production rates up to 90 tons per hour.

Diamond Z Grinders, Caldwell Idaho

www.diamondz.com

208-585-2929

۲

SPECIFICATIONS:





DZH4000

DZH4000TK D

DZH4000TKT

۲

POWER:	CAT [®] C18 755 HP Tier 4	CAT [®] C18 755 HP Tier 4	CAT [®] C18 755 HP Tier 4
TRANSMISSION:	Fluid Coupling Drive	Fluid Coupling Drive	Fluid Coupling Drive
TRANSPORT DIMENSIONS (L x W x H):	42'-0" x 9'-9" x 13'-7"	41'-5" x 10'-3" x 12'-0"	47'-10" x 11'-4" x 13'-4"
OPERATING DIMENSIONS (L x W x H):	61'-0" x 10'-0" x 18'-0"	50'-2" x 10'-4" x 14'-0"	46'-0" x 10'-0" x 14'-0"
WEIGHT:	78,500 Lbs.	85,000 Lbs.	98,000 Lbs.
MILL FEED OPENING (W x H):	54.5" x 48"	54.5" x 48"	54.5" x 48"
SCREEN AREA:	3,800 Sq. In.	3,800 Sq. In.	3,800 Sq. In.
PRODUCTION:	Up to 120 TPH/475 YPH	Up to 120 TPH/475 YPH	Up to 120 TPH/475 YPH

STANDARD FEATURES: Radio remote control, Fluid coupling mill drive, reversing fan, tool box, engine cover and super-screw belt lacing. All track mounted machines come with 24" (600mm) wide pads, other options available.

All information subject to change without notice. Please reconfirm any critical details. Productions rates based on customer reports, actual throughput will vary depending on on-site specifics.

4000-0620